

KING-PIN WALKING FOOT

THE FUTURE OF RIG WALKING



OVERVIEW

Entro King-Pin Walking feet are uniquely suited to rigs where conventional walking feet do not perform well. The patented design allows a large sized foot to be placed in confined areas while still allowing the rig to move in **ANY DIRECTION**. It is extremely well-suited to being integrated into the substructure of a rig.

- Adjust steering direction with the included 3/4" ratchet; simple steering dog locks in the desired steering angle
- Linkage maintains foot alignment to sub, while King-Pin allows roller to steer in any direction
- The King-Pin includes spring-loaded guides to ensure precise steering, overload protection and long life
- King-Pin feet will fit into any location a conventional foot will fit
- Electronic power steering available

TECHNICAL SPECIFICATIONS

JACK CAPACITY	875,000 lbs / 600,000 lbs Capacities Standard
TOTAL CAPACITY	NO LIMIT
CYCLE TIME	60 Seconds
DISTANCE PER STEP	24" Travel Standard (other sizes available)
JACKS	15" Lift Standard
WALKING FEET (SIZE)	Engineered to Fit
ROLLERS	Custom Hilman
STEERING	Manual (Standard) / Electronic Power Steering (Optional)
RIG CONNECTION	Pins / Bolts onto Substructure
HYDRAULICS	Compatible with Rig HPU / Dedicated HPU Optional

PATENTS:

This product may be protected by one or more patents and applications.

For more information, see entro-eng.com/about/patents/

3601 NE John Olsen Avenue, Hillsboro, OR 97124
OFFICE: (503) 356-8888 EMAIL: info@entro-eng.com
WWW.ENTRO-ENG.COM

ENTRO
INDUSTRIES