

# LOW PRO WALKERS



## OVERVIEW

Entro Low Pro Walkers are designed to be used with single piece substructures with below grade well completions. The Low Pro Walkers allow the drilling contractor to move not only a substructure with full setback, but also the water tank and mud tanks as well. This allows movement without requiring rig down.

- Custom engineered to fit your rig
- Simple installation
- Entire system rigs up without cranes
- Low ground bearing pressures under walking foot
- All Entro walkers can move in any direction, as well as spin your rig in place
- Hydraulic hoses and piping are factory assembled, labeled, and tested with quick disconnects at console
- Wireless remote control with manual backup; spare remote included as standard
- System can be customized at customer request
- Direct replacement for skidding systems

## TECHNICAL SPECIFICATIONS

CAPACITY	1.5 Million lbs (shown) / (other sizes available)
CYCLE TIME	60 Seconds
DISTANCE PER STEP	24" Travel
JACKS	15" Lift
WALKING FEET (SIZE)	Engineered to Fit
ROLLERS	Custom Hilman
STEERING	Manual (Standard) / Electronic Power Steering (Optional)
STRUCTURE	(2) Jack Support Frames
RIG CONNECTION	Substructure Pins Down to Walker
HYDRAULICS	Compatible with Rig HPU / Dedicated HPU Optional

### PATENTS:

This product may be protected by one or more patents and applications.

For more information, see [entro-eng.com/about/patents/](http://entro-eng.com/about/patents/)

3601 NE John Olsen Avenue, Hillsboro, OR 97124  
OFFICE: (503) 356-8888 EMAIL: [info@entro-eng.com](mailto:info@entro-eng.com)  
[WWW.ENTRO-ENG.COM](http://WWW.ENTRO-ENG.COM)

**ENTRO**  
INDUSTRIES